

Hampton Controls

1-800-437-2664

www.hamptoncontrols.com

## **COL** Gold Label Series 50 Amps

Durakool Gold Label 35 and 50 Amp models (normally open) are economical, special purpose contactors developed to handle resistive loads over millions of switching cycles. They have been used successfully in commercial cooking equipment, plastics machinery, process heating controls, comfort heating and lighting control applications.

As in all Durakool contactors, the liquid contact action of mercury switching is far superior to conventional mechanical contactors, offering significantly longer life. Gold Label contactors operate dependably in harsh industrial/commercial environments without special protection and do not require sophisticated equipment for troubleshooting.

## SPECIFICATIONS

Maximum Time: Operate Release 70 ms 90 ms

Contact Bounce, Release: None

Recommended

DC Load Polarity: Top Connector Negative Load Connectors: Pressure Connector 4-14

AWG Cu.

Coil Terminals: '6-32 Wire Binding Screw,

Max. \*12 AWG Cu.

Breakdown Voltage: 2000 VRMS/Min. Across

Contacts



TYPE/SERIES	Gold Label (50 Amps)							
DESCRIPTION		Resistive Part Number	Typical Coil Data DC OhmsWatts Amps V.A.					
	Volts							
1 Pole	24	1050A24AC	40	2.74	0.229	5.50		
(Normally Open)	120	1050A120AC	902	3.57	0.056	6.72		
	208	1050A208AC	3100	3.35	0.029	6.03		
	240	1050A240AC	3700	3.02	0.024	5.76		
	277	1050A277AC	5410	3.28	0.021	5.82		
	480	1050A480AC	15000	3.42	0.012	5.76		
	12(00)	1050A12DC	40	3.47	0.288	_		
	24(00)	1050A24DC	230	2.50	0.104	_		

ELECTRICAL RATINGS	GENERAL PURPOSE 0.7/0.8 UL Power Factor					DC			Tungsten Lamp/60 Hz		
Volts	120	208	240	277	480	600	1-48	120	20 240 120		0
SERIES	60 Hz AC Amps					DC Amps			Amps	KW	
GL 50A (Normally Open)	35	50	50	50	50	50	50	25	15	50	6.0



www.hamptoncontrols.com

## **URAKOOL** Gold Label Series 50 Amps



